

LIS009636759B2

(12) United States Patent Buob

(10) Patent No.:

US 9,636,759 B2

(45) **Date of Patent:**

May 2, 2017

(54) CRANKSHAFT MILLING CUTTER

(71) Applicant: Walter AG, Tübingen (DE)

(72) Inventor: Rolf Buob, Horb (DE)

(73) Assignee: Walter AG, Tübingen (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 173 days.

(21) Appl. No.: 14/377,907

(22) PCT Filed: Mar. 22, 2013

(86) PCT No.: PCT/EP2013/056131

§ 371 (c)(1),

(2) Date: Aug. 11, 2014

(87) PCT Pub. No.: WO2013/144030

PCT Pub. Date: Oct. 3, 2013

(65) Prior Publication Data

US 2015/0037107 A1 Feb. 5, 2015

(30) Foreign Application Priority Data

Mar. 29, 2012 (DE) 10 2012 102 747

(51) Int. Cl.

B23C 3/06 (2006.01) **B23C 5/24** (2006.01) **B23C 5/08** (2006.01)

(52) U.S. Cl.

CPC *B23C 5/2462* (2013.01); *B23C 5/08* (2013.01); *B23C 5/241* (2013.01); *B23C 5/2489* (2013.01);

(Continued)

(58) Field of Classification Search

CPC B23C 2215/20; B23C 5/08; B23C 5/241; B23C 5/2462; B23C 5/2489; B23C 5/207; (Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

4,938,638 A 7/1990 Hessman et al.

5,919,008 A * 7/1999 Shimomura B23C 3/06 407/35

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1035786 9/1989 CN 1671501 9/2005 (Continued)

OTHER PUBLICATIONS

English translation of Notification of First Office Action for Chinese Application No. 201380018153.2 dated Nov. 13, 2015.

(Continued)

Primary Examiner — Sara Addisu (74) Attorney, Agent, or Firm — Morgan, Lewis & Bockius LLP

(57) ABSTRACT

A crankshaft milling cutter has a disc-shaped main body rotatable about an axis perpendicular to the disc plane and on the periphery recesses for receiving indexable cutting inserts for removing an allowance on the crankshaft blank. At least some of the recesses are open both in the radial direction and in at least one axial direction of the main body and a first group of said recesses receives cutting inserts designed for removing the allowance on an oil collar adjoining a shaft journal. To provide a crankshaft milling cutter able to meet the increasing requirements with regard to dimensional and positional tolerances placed on a crankshaft milling cutter and at the same time reduces the time needed for fine adjustment of the crankshaft milling cutter, only some of the first group of recesses has devices for setting the axial position of the indexable cutting insert received in each case therein.

27 Claims, 3 Drawing Sheets



